





TN1600

Tissue embedding station

The space saving TN1600 tissue embedding station is a complete system, consisting of a paraffin dispenser and cold plate module. The ergonomically designed working area is illuminated with LED lights and offers a comfortable working environment. An intuitive control panel enables easy and logical control of the system. 2 heated trays with elevated lids provide a prewarming capacity of up to 106 cassettes and 288 embedding molds. The smaller footprint TN1600 is ideal for the demands of low to mid-volume laboratories.

Highlights


- Manual lever and foot switch for paraffin dispensing
- Adjustable magnifying glass
- Ergonomic hand rest
- Spacious and heated paraffin collection tray
- 3.8 liters paraffin container
- Cooling spot
- Two heating trays for 106 cassettes and 288 embedding molds.
- Ergonomic working height
- Working area with LED light
- Intuitive control panel
- Electrically heated forceps (optional)
- Integrated heated wax trimmer:
 - efficiently removes excess paraffin from any embedding tissue cassette
 - paraffin is easily melted away and drains into the removable tray below
 - physical damages by conventional trimming tools such as knife or razor are avoided consequently
 - large scale design of the trimmer area allows paraffin trimming of multiple blocks simultaneously





All in reach

2 heated trays for either 106 standard cassettes or 288 embedding molds are conveniently located at the back of the working area.



Standard Components
Heated paraffin (wax) container
Heated dispenser element
Heated cassette/mold storage containers
Heated working area
Cooling spot
Magnifying glass, adjustable
Paraffin collection tray
Working area illumination (LED)
Operation manual

Specifications	
Paraffin container	3.8 liters
Heated cassette/ mold container Processing	Up to 106 cassettes Up to 288 molds 30–80°C programmable
Dimensions (width x depth x height)	17-3/4" x 22-1/2" x 11-1/2"
Weight without accessories	50 lbs

TN1600 115 V, 50/60 Hz	Item # TNR TN1600

TN1700

Modular paraffin embedding center

The TN1700 features a spacious working area, large container capacity and industry leading reliability. All modules operate at the same working height and can be arranged according to laboratory requirements. The extendable modular 3-component system with separate temperature control elements consists of a dispensing element TN1700A, a preheating unit TN1700C and a separate cooling plate (TNCST: standard size or TNCXL: x-large size available)



Highlights

- Spacious cooling plate
- Adjustable magnifying glass
- Ergonomic hand rest
- Programmable working hours
- Easily adjustable forceps holders
- 5.5 liters paraffin container
- Spacious and heated paraffin collection tray
- Working area with adjustable LED-illumination and integrated cold spot
- Electrically heated forceps (optional)
- Integrated heated wax trimmer:
 - efficiently removes excess paraffin from any embedding tissue cassette
 - paraffin is easily melted away and drains into the removable tray below
 - physical damages by conventional trimming tools such as knife or razor are avoided consequently
 - large scale design of the trimmer area allows paraffin trimming of multiple blocks simultaneously

Standard components

Dispensing module TN1700A

Prewarming unit TN1700C

Cooling unit TNCST (TNCXL - Available as Upgrade)

Foot switch for paraffin dispenser

Forceps holder

2x forceps (1x blunt, 1x pointed)

Cleaning spattle black

Base molds 7 x 7 x 7 mm, 12 pcs., stainless steel

Base molds 24 x 24 x 7 mm, 12 pcs., stainless steel

Power cord

Operation manual

TN1700 115V 50/60 Hz

Item # TNR TN1700



TN1700A Dispensing module (Large)



Spacious

Large working area with integrated cold spot. The working area has a special drainage system and guides the paraffin into the heated collection tray.



included, easy to orientate

working time, time, date

Under Control

The 5.5-liter volume allows constant working with the TN1700A. The perfect light and easily regulated flow keeps everything under control.



Specifications

Magnifier

Temperature range up to 80°C (1°C increments)
for paraffin container
up to 70 °C (1°C increments)
for working area
down to -10°C for cooling spot

Capacity 5.5 liter paraffin

Cooling spot 2" x 2", peltier

Forceps holders 2 x 4 adjustable (magnetic)

Illumination 3 LED spots fixed + 3 LED spots adjustable

Paraffin flow

activation manually or by footswitch continuously adjustable flow rate

Control

microprocessor, programming of temperature, working day,

Work area 17-3/4" x 9-1/2"

Dimensions 17-3/4" x 22-1/2" x 11-5/8" (width x depth x height)

Weight 46 lbs

Electrical parameters 115, 50/60 Hz

Consumption P_{max}: 380 W

Temperature 18–35°C, air conditioned room recommended

Humidity < 60%

Cold Plate Configurations

TNR TNCST: Standard Cold Plate



TNR TNCXL: X-Large Cold Plate (Available as Upgrade)



TN1700A 115V 50/60 Hz

Item # TNR TN1700A

TN1700C Prewarming unit



Mold warmer

To have enough molds ready for the large working area of the TN1700A, the TN1700C has a mold warmer for up to 500 molds. Temperature freely selectable up to 80°C.



Cassettes

Take common baskets (like from the MTM tissue processor) and place them directly in the cassette bath. This is workflow efficiency.



Easy to clean

The cassette bath can be taken out for cleaning. So, disposal of paraffin is easy.



Independent

The TN1700C works independently from the TN1700A. So, you have full modularity and flexibility as you can place the unit wherever needed.



Specifications	
Temperature range	up to 80°C (1°C increments) for working area
Cassette bath	Capacity 150 cassettes, removable 9-7/8" x 10-1/4" x 1-1/4"
Control	microprocessor, programming of temperature, working day, working time, time, date
Mold warmer	Capacity 500 molds 10-1/4" x 8-11/16" x 2-3/4"
Dimensions (width x depth x height) Weight	11-5/16" x 22-7/16" x 11-5/8" 33 lbs
Power	115 V, 50/60 Hz
Consumption	P _{max} : 320 W
Temperature	18–35°C, air conditioned room recommended
Humidity	< 60%

TN1700B 115V 50/60 Hz Item # TNR TN1700B

TNCST / TNCXL

Cooling units





Upgrade: TNCXL

Independent

Truly modular. Due to the independent control, you can place the module wherever the cold plate is needed.



Specifications	
Temperature range	min15°C (1°C increments)
Max. capacity	TNCST Up to 80 cassettes
	TNCXL Up to 120 cassettes
Control	microprocessor, programming of temperature, working day, working time, time, date
Work area	TNCST 14-9/16" x 10-5/8"
	TNCXL 22-7/16" x 10-5/8"
Dimensions (width x depth x height)	TNCST 15-3/4" x 22-7/16" x 11-5/8"
	TNCXL 23-5/8" x 22-7/16" x 11-5/8"
Weight	TNCST 55 lbs
	TNCXL 79 lbs

Electrical parameters	115 V, 50/60 Hz
Consumption	TNCST Pmax: 150 W TNCXL Pmax: 250 W
Temperature	18–35°C, air conditioned room recommended
Humidity	< 60%

Accessories

Call 800.331.2716 for more info.

TN1700C 115 V 60 Hz	Item # TNR TN1700C
TN1700D 115 V 60 Hz	Item # TNR TN1700D

Mercedes Scientific

12210 Rangeland Parkway Lakewood Ranch, FL 34211

Phone: 800.331.2716 Fax: 800.359.8807

www.MercedesScientific.com

